

# Data sheet



## Suggestion for installation and cleaning of ULTRATOP filter cartridges

Ø mm	L mm	Filter area m <sup>2</sup>	Clean. method	Cartridges / valve				Air pressure bar	Air volume norm litre	On-time sec.	Venturi		Blow bare	
				¾"	1.0 "	1.5 "	2.0 "				height	Ø	hole	Distan
150	600	2.2	Jet	5	9	xxx	xxx	4.5 -,5.0	3 - 6	0.1 - 0.3	110	105	9	65
	1000	3.6	Jet	3	5	9	xxx	4.5 - 5.0	5 - 10	0.1 - 0.3	110	105	9	65
	1200	4.3	Jet	2	3	7	xxx	4.5 - 5.0	6 - 12	0.1 - 0.3	110	105	9	65
	1400	5	Jet	2	3	6	xxx	4.5 - 5.0	7 - 14	0.1 - 0.3	110	105	9	65
225	600	3	Jet	3	5	9	xxx	5.0 - 5.5	4 - 9	0.1 - 0.3	160	150	12	100
	1000	5	Jet	2	4	6	xxx	5.0 - 5.5	7 - 15	0.1 - 0.3	160	150	12	100
	1200	6	Jet	1	2	4	6	5.0 - 5.5	8 - 18	0.1 - 0.3	160	150	12	100
	1400	7	Jet	1	2	3	5	5.0 - 5.5	10- 21	0.1 - 0.3	160	150	12	100
325	600	7.8	Jet	1	2	3	4	5.5 - 6.0	12 - 25	0.1 - 0.3	160	210	16	120
			RSD	1	2	xxx	xxx	3.5 - 4.0	40 - 50	0.5 - 4.0	xxx	xxx	xxx	xxx
	1000	13	RSD	1	2	xxx	xxx	3.5 - 4.0	65 - 80	0.5 - 4.0	xxx	xxx	xxx	xxx
			Jet	xxx	1	2	3	5.5 - 6.0	20 - 35	0.1 - 0.3	160	210	16	120
	1200	15.6	RSD	1	2	xxx	xxx	3.5 - 4.0	80 - 100	0.5 - 4.0	xxx	xxx	xxx	xxx
			Jet	xxx	1	2	3	5.5 - 6.0	25 - 45	0.1 - 0.3	160	210	16	120
	1400	18.2	Jet	xxx	1	2	3	5.5 - 6.0	30 - 50	0.1 - 0.3	160	210	16	120

- Schutzvermerk nach ISO 16016 – Protection notice as per ISO 16016 -